

Model	2U20ATX400XR-2	2U26ATX400XR-2	3U25ATX450XR-2	3U25EPS550XR-2	4U22ATX450-2	4U22EPS550-2
Description	19" Rackmount, 2U		19" Rackmount, 3U		19" Rackmount, 4U	
Power Supply	ATX 12V 400W SmartPower2.0		ATX12V 450W SmartPower2.0	EPS12V 550W TruePower2.0	ATX12V 450W Smart Power2.0	EPS12V 550W TruePower2.0
Motherboard	Standard ATX up to 12" x 9.6"	Extended ATX up to 12" x 13"	Extended ATX up to 12" x 13" Dual Xeon(EEB & CEB ready)		Extended ATX up to 12" x 13" Dual Xeon(EEB & CEB ready)	
Dims.(H x W x D)	3.5"H x 17"W x 19.7"D	3.5"H x 17"W x 25.6"D	5.2"H x 17"W x 25"D	5.2"H x 17"W x 25"D	7"H x 17"Wx 22"D	
Ext. Drive Bays	1 x 5.25" + 1 x 3.5"		4 x 5.25" + 2 x 3.5"	3 x 5.25" + 2 x 3.5"	3x5.25" + 3x3.5" (with 120mm Fan) *	
Int. Drive Bays	3 x 3.5"	5 x 3.5"	4 x 3.5"		7 x 3.5" *	
Expansion Slots	2 expansion slots, PCI Riser Card included		7 expansion slots (7 long card)			
Cooling System	1 x 60mm + 1 x 80mm Ball bearing fans	1 x 60mm + 3 x 80mm Ball bearing fans	1 x 80mm + 3 x 92mm Ball bearing fans		1 x 120mm intake fan (Default) + 2 x 80mm ball bearing exhaust fans	
Front USB ports	N/A		Dual front USB socket with shielded cable			
Weight/Net Gross	20 / 27 lbs	25 / 32 lbs	32 / 43 lbs	33 / 43 lbs	38 / 49 lbs	38 / 50 lbs
UCC# - US	0761345-94229-4	0761345-94230-0	0761345-94324-6	0761345-94327-7	0761345-94402-1	0761345-94552-3
UCC# - EC	0761345-02203-3	0761345-02263-7	0761345-03207-0	0761345-03257-5	0761345-04223-9	0761345-04227-7
UCC# - UK	0761345-02204-0	0761345-02264-4	0761345-03208-7	0761345-03258-2	0761345-04224-6	0761345-04228-4

* alternate drive configuration for 4U models: 6 x 5.25" and 3 x 3.5" external drive bays, with 3 x 3.5" internal drive bays and no 120mm intake fan.